



HOW ARE WE DIFFERENT?

CDC Guidelines on Vaccine Storage

Released May 2014

1. **Digital display on outside of storage unit.**
 - LCD Display with temperature/humidity reading and battery level
2. **Detachable probe in a bottle filled with thermal buffer, like glycol, which more closely reflects vaccine temperatures.**
 - Glycol Product Simulator
 - Internal & External Thermistor Probe for Ambient
 - RTD Probe (Resistance Temperature Detector)
3. **Alarm to alert out-of-range temperatures**
 - Alarms via Email, Text Message, or Phone Call
4. **Accuracy within +/-1°F (+/- .5°C)**
 - SMART Guard® meets this requirement
5. **Low battery indicator**
 - Emailed alerts when AA batteries reach 20%
6. **Continuous monitoring and recording capabilities to track and record temperatures over time**
 - Logs 24/7/365 and SMART Command Center® Website saves data for 7 years
7. **Minimum and maximum temperatures**
 - SMART Command Center Website show a minimum and maximum temperature with a 24 hour average
8. **ISO 17025 calibrated temperature monitoring devices with a NIST Certificate of Traceability**
 - NIST Traceability and ISO 17025 Calibration Certificates available for SMART Guard and thermistor probes.

SMART Temps is a very customer focused company. Our team works in-house each day, training customer staff members, answering questions, running reports, etc. We are not just a product offering, like most other vendors, we make sure our customers are set-up and know how to use our products.

Contact SMART Temps today for your 30-day trial.

877-272-3111 | SMART-Temps.com



LCD Display

- Temperature/ Humidity
- Battery Level

Battery Level

- At 20% Email Alert Sent

(3) AA Batteries

- Est. to last about 12-14 months

Detachable External Probes

- Glycol Product Simulator
- Thermistor Probe
- RTD Probe
- Door Switch



Patented Communication

Web-based Reporting Tool

- View all locations/sites using desktop or mobile devices.
- SMART Temps hosts all data
- Data does not reside on company servers alleviating the chance of HIPPA violations or data breaches.

Send Data via Ethernet, Wi-Fi, or Cellular

Return on Investment

Customized Alert Settings

- Example: Set alerts by time of day, have maintenance be alerted in the evening.

In-Range % Report

- Calculates the % each piece of equipment is in its proper temperature range.
- With the data collected, if a piece of equipment is operating at a higher level than needed, turn down the unit and save energy.